




IS119/IS119b

The IS119 is the larger subwoofer in the IS-Series. The enclosure is loaded with a light weight, long excursion, 19" ND19-S Kevlar Neodymium driver utilizing Adamson's Advanced Cone Architecture. It is mounted in an ultra-efficient front-loaded enclosure, designed to reproduce clean, musical low frequency information.


The cabinet construction uses marine grade birch plywood as well as aircraft grade aluminum and steel, and is equipped with two front and back Speakon™ NL4 connectors (IS119), or barrier strips (IS119b). A dual grill solution is used so that when arranged in cardioid mode, the appearance does not change. The integrated rigging system matches the rigging for the IS10 and can be flown in the same array using the IS10 & IS119 Support Frame. (930-0028)

Specifications


Frequency Range (+/- 3dB)	30 Hz - 100 Hz
Maximum Peak SPL**	138 dB
Components LF	ND19 19" Kevlar Neodymium Driver
Nominal Impedance LF	8 Ω
Power Handling (AES / Peak) LF	1200 / 4800 W
Rigging	Integrated Rigging System
Connection	4x Speakon™ NL4 (2x Front 1+/1-, 2x Rear (2+/2-), or Barrier Strips
Height Front (mm / in)	544 / 21.4
Width (mm / in)	737 / 29
Depth (mm / in)	645 / 25.4
Weight (kg / lbs)	44.5 / 98
Colour	Black & White (Standard), RAL Colours (On Demand)
Processing	Lake



737 mm / 29 in



645 mm / 25.4 in



544 mm / 21.4 in

**12 dB crest factor pink noise at 1m, half space, using specified processing and amplification